



SILVER EAGLE

2734, 2744, 2550, 2750 & 2760HP

Whether maintaining your lawn or commercial mowing, the Silver Eagle line of mowers will fill your needs. Backed by the best warranty in the industry, the Silver Eagle line of zero-turn mowers will deliver all the features the professionals use, at affordable pricing.

Up to a
5 Year
WARRANTY
Including a
3,000 Hour
Drivetrain Warranty
(See dealer for details)



Deck & Spindle

Anti-scalp rollers
Adjustable baffles
One piece keyless spindle housing
1.25" effective diameter spindle
Replaceable top plate

Fully adjustable
suspension seat
with armrest
(Silver Eagle 2760HP only)

Stainless
steel body

Turf Master Tires
24 Inch

Flip-up floor pan
with rubber mat

OCDC
Operator Controlled Discharge Chute

Anti-scalp rollers

Silver Eagle 2760HP Shown

Models	Engine Horsepower	Deck Sizes	Acres Per Hour	Fuel Capacity
Silver Eagle 2734	Generac 27HP	34 Inches	2.7 Acres Per Hour	8 Gallons
Silver Eagle 2744	Generac 27HP	44 Inches	3.5 Acres Per Hour	8 Gallons
Silver Eagle 2550	Kohler 25HP	50 Inches	4.0 Acres Per Hour	8 Gallons
Silver Eagle 2750	Generac 27HP	50 Inches	4.0 Acres Per Hour	8 Gallons
Silver Eagle 2760HP	Generac 27HP	60 Inches	5.3 Acres Per Hour	8 Gallons

Acres per hour is calculated on 80% operator accuracy and mowing conditions. Optimum cutting height 2.5" to 4.5" outside that range minor adjustment may be required. Visit dixiechopper.com or your local Dixie Chopper dealer for more information.

Revision 10/17/2011
Part Number 700210



SILVER EAGLE

2734

2744

2550

2750

2760^{HP}

Engine					
Manufacturer	Generac	Generac	Kohler	Generac	Generac
Horsepower*	27HP @ 3750RPM	27HP @ 3750RPM	25HP @ 3750RPM	27HP @ 3750RPM	27HP @ 3750RPM
Displacement	762cc	762cc	725cc	762cc	762cc
Crankshaft	Vertical Shaft	Vertical Shaft	Vertical Shaft	Vertical Shaft	Vertical Shaft
Oil System	Gear-Driven	Gear-Driven	Gear-Driven	Gear-Driven	Gear-Driven
Oil Safety Features	Low oil warning horn (98db)	Low oil warning horn (98db)	N/A	Low oil warning horn (98db)	Low oil warning horn (98db)
Additional Filtration	N/A	N/A	N/A	N/A	N/A
Air-Cleaner	Dual Stage Donaldson	Dual Stage Donaldson	Kohler Air-Filter	Dual Stage Donaldson	Dual Stage Donaldson
Cooling	Air Cooled	Air Cooled	Air Cooled	Air Cooled	Air Cooled
Electrical					
Battery	12 Volt, 300cca - Standard	12 Volt, 300cca - Standard	12 Volt, 300cca - Standard	12 Volt, 300cca - Standard	12 Volt, 300cca - Standard
Charging System	20 Amp Alternator	20 Amp Alternator	20 Amp Alternator	20 Amp Alternator	20 Amp Alternator
Presence Control	Seat Switch Safety Shut-off	Seat Switch Safety Shut-off	Seat Switch Safety Shut-off	Seat Switch Safety Shut-off	Seat Switch Safety Shut-off
Hour Meter	Digital, Tachometer, Voltmeter, Service Alerts	Digital, Tachometer, Voltmeter, Service Alerts	Digital, Tachometer, Voltmeter, Service Alerts	Digital, Tachometer, Voltmeter, Service Alerts	Digital, Tachometer, Voltmeter, Service Alerts
Fuel System					
Fuel Type	Gasoline	Gasoline	Gasoline	Gasoline	Gasoline
Fuel Gauge	N/A	N/A	N/A	N/A	N/A
Fuel Capacity	8 Gallon	8 Gallon	8 Gallon	8 Gallon	8 Gallon
Fuel Valve	3 Position/Shut-off	3 Position/Shut-off	3 Position/Shut-off	3 Position/Shut-off	3 Position/Shut-off
Drive System					
Transaxle	N/A	N/A	N/A	N/A	N/A
Torqpack	N/A	N/A	N/A	N/A	N/A
Pump	Hydro-Gear 10 Series	Hydro-Gear 10 Series	Hydro-Gear 10 Series	Hydro-Gear 10 Series	Hydro-Gear 12 Series
Wheelmotors	Parker 240 Series	Parker 240 Series	Parker 240 Series	Parker 240 Series	Parker 240 Series
Controls					
Directional Control	Independent Steering Levers	Independent Steering Levers	Independent Steering Levers	Independent Steering Levers	Independent Steering Levers
Blade Engagement	PTO Switch	PTO Switch	PTO Switch	PTO Switch	PTO Switch
Deck Height Adjustments	Manual Lift, 1/4" increments	Manual Lift, 1/4" increments	Manual Lift, 1/4" increments	Manual Lift, 1/4" increments	Electric Lift, 1/4" increments
Ignition	Key Switch	Key Switch	Key Switch	Key Switch	Key Switch
Throttle/Choke	Standard	Standard	Standard	Standard	Standard
Deck Deflector	OCDC - Operator Controlled Discharge Chute	OCDC - Operator Controlled Discharge Chute	OCDC - Operator Controlled Discharge Chute	OCDC - Operator Controlled Discharge Chute	OCDC - Operator Controlled Discharge Chute
Parking Brake	Standard - Drum	Standard - Drum	Standard - Drum	Standard - Drum	Standard - Drum
Body					
Frame	Welded 2X2 Tube, 7ga Formed	Welded 2X2 Tube, 7ga Formed	Welded 2X2 Tube, 7ga Formed	Welded 2X2 Tube, 7ga Formed	Welded 2X2 Tube, 7ga Formed
Fenders	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Floor-pan	Flip-up, Steel with rubber mat	Flip-up, Steel with rubber mat	Flip-up, Steel with rubber mat	Flip-up, Steel with rubber mat	Flip-up, Steel with rubber mat
Seat	Standard Seat with Armrest	Standard Seat with Armrest	Standard Seat with Armrest	Standard Seat with Armrest	Deluxe Suspension Seat with Armrest
Engine Guard	Standard	Standard	Standard	Standard	Standard
Towing Capacity	500 lbs (with optional hitch)	500 lbs (with optional hitch)	500 lbs (with optional hitch)	500 lbs (with optional hitch)	500 lbs (with optional hitch)
Mower Deck					
Deck Size	34 Inches	44 Inches	50 Inches	50 Inches	60 Inches
Construction	7 ga (.187") Formed & Welded	7 ga (.187") Formed & Welded	10 ga (.135") Formed & Welded	10 ga (.135") Formed & Welded	10 ga (.135") Formed & Welded
Top Plate	N/A	N/A	7 ga bolted not welded	7 ga bolted not welded	7 ga bolted not welded
Blades	3-14.5 Inch Blades	3-17 Inch Blades	3-17 Inch Blades	3-17 Inch Blades	3-20.5 Inch Blades
Tip Speed (Approximate)	16,015 fpm	18,776 fpm	18,776 fpm	18,776 fpm	18,113 fpm
Spindle Housings	1pc Keyless Sealed Cast Iron	1pc Keyless Sealed Cast Iron	1pc Keyless Sealed Cast Iron	1pc Keyless Sealed Cast Iron	1pc Keyless Sealed Cast Iron
Spindles	1.25" Effective diameter machined shaft	1.25" Effective diameter machined shaft	1.25" Effective diameter machined shaft	1.25" Effective diameter machined shaft	1.25" Effective diameter machined shaft
Anti-Scalp Rollers	Standard	Standard	Standard	Standard	Standard
Pulleys	Vented Split 3/16" Steel Deep Groove	Vented Split 3/16" Steel Deep Groove	Vented Split 3/16" Steel Deep Groove	Vented Split 3/16" Steel Deep Groove	Vented Split 3/16" Steel Deep Groove
Electric Deck Lift	Optional	Optional	Optional	Optional	Standard
Deck Quick Lift	Optional	Optional	Optional	Optional	Standard
Tires					
Rear Tires	24X7-10 Turf Boss V Tubeless 4ply	24X12-12 Turf Master Tubeless 4ply	24X12-12 Turf Master Tubeless 4ply	24X12-12 Turf Master Tubeless 4ply	24X12-12 Turf Master Tubeless 4ply
Front Tires	13X6.5-6 Tubeless 4ply	13X6.5-6 Tubeless 4ply	13X6.5-6 Tubeless 4ply	13X6.5-6 Tubeless 4ply	13X6.5-6 Tubeless 4ply
Dimensions & Performance (Approximate)					
Acres/Hour	2.7 Acres Per Hour	3.5 Acres Per Hour	4.0 Acres Per Hour	4.0 Acres Per Hour	5.3 Acres Per Hour
Cutting Height	1.5 Inches to 5 Inches	1.5 Inches to 5 Inches	1.5 Inches to 5 Inches	1.5 Inches to 5 Inches	1.5 Inches to 5 Inches
Overall Height (with rollbar up)	72 Inches	73 Inches	73 Inches	73 Inches	73 Inches
Overall Height (with rollbar down)	48 Inches	49 Inches	48 Inches	48 Inches	48 Inches
Overall Width	39 Inches	49 Inches	54 Inches	54 Inches	65 Inches
Overall Length (with rollbar up)	76 Inches	76 Inches	74 Inches	74 Inches	74 Inches
Overall Length (with rollbar down)	96 Inches	96 Inches	94 Inches	94 Inches	94 Inches
Overall Weight	970 Pounds	1042 Pounds	1084 Pounds	1104 Pounds	1215 Pounds

Specifications may change as we continually improve our mowers. For the latest information and mower specifications, please visit dixiechopper.com or visit your local Dixie Chopper dealer.
*The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only.

Revision 10/17//2011