



XCALIBER

3366, 3374 & 4074

Whether you need to be king of commercial cutting or just king of your own lawn, the Xcaliber series of mowers is for you. Featuring high horsepower engines and a deep tunnel deck, the Xcaliber machines are engineered for speed, power and reliability.

Up to a
5 Year
WARRANTY
Including a
3,000 Hour
Drivetrain Warranty
(See dealer for details)



Deck & Spindle

Revolutionary wind tunnel
Anti-scalp rollers
Adjustable baffles
One piece keyless spindle housing
1.25" effective diameter spindle
Replaceable top plate



- Certified "halo" style roll bar
- Fully adjustable suspension seat with armrest
- Control panel
- 12 Volt accessory plug
- Turf Boss Tires
- Stainless steel body
- Flip-up floor pan with rubber mat
- Anti-scalp rollers
- Springer front forks
- OCDC Operator Controlled Discharge Chute

Xcaliber 3366 Shown

Models	Engine Horsepower	Deck Sizes	Acres Per Hour	Fuel Capacity
Xcaliber 3366	Generac 33HP	66 Inches	5.9 Acres Per Hour	14 Gallons
Xcaliber 3374	Generac 33HP	74 Inches	6.6 Acres Per Hour	14 Gallons
Xcaliber 4074	Kohler 40HP	74 Inches	6.6 Acres Per Hour	14 Gallons

Acres per hour is calculated on 80% operator accuracy and mowing conditions. Optimum cutting height 2.5" to 4.5" outside that range minor adjustment may be required. Visit dixiechopper.com or your local Dixie Chopper dealer for more information.

Revision 09/09/2011
Part Number 700212



XCALIBER

3366

3374

4074

Engine			
Manufacturer	Generac	Generac	Kohler
Horsepower*	33HP @ 3750RPM	33HP @ 3750RPM	40HP @ 3750RPM
Displacement	992cc	992cc	999cc
Crankshaft	Vertical Shaft	Vertical Shaft	Vertical Shaft
Oil System	Gear-Driven	Gear-Driven	Gear-Driven
Oil Safety Features	Low oil warning horn (98db)	Low oil warning horn (98db)	N/A
Additional Filtration	Amsoil 1 Micron Filter	Amsoil 1 Micron Filter	N/A
Air-Cleaner	Donaldson Dual Stage	Donaldson Dual Stage	Dual Stage
Cooling	Air Cooled	Air Cooled	Air Cooled
Electrical			
Battery	12 Volt, 475cca - Standard	12 Volt, 475cca - Standard	12 Volt, 475cca - Standard
Charging System	20 Amp Alternator	20 Amp Alternator	20 Amp Alternator
Presence Control	Seat Switch Safety Shut-off	Seat Switch Safety Shut-off	Seat Switch Safety Shut-off
Hour Meter	Digital, Tachometer, Voltmeter, Service Alerts	Digital, Tachometer, Voltmeter, Service Alerts	Digital, Tachometer, Voltmeter, Service Alerts
Fuel System			
Fuel Type	Gasoline	Gasoline	Gasoline
Fuel Gauge	N/A	N/A	N/A
Fuel Capacity	14 Gallon	14 Gallon	14 Gallon
Fuel Valve	3 Position/Shut-off	3 Position/Shut-off	3 Position/Shut-off
Drive System			
Transaxle	N/A	N/A	N/A
Torgpact	N/A	N/A	N/A
Pumps	Hydro-Gear 21 Series	Hydro-Gear 21 Series	Hydro-Gear 21 Series
Wheelmotors	White 24 Cubic Inch	White 24 Cubic Inch	White 24 Cubic Inch
Controls			
Directional Control	Independent Steering Levers	Independent Steering Levers	Independent Steering Levers
Blade Engagement	PTO Switch	PTO Switch	PTO Switch
Deck Height Adjustments	Electric Lift, 1/4" increments	Electric Lift, 1/4" increments	Electric Lift, 1/4" increments
Ignition	Key Switch	Key Switch	Key Switch
Throttle/Choke	Standard	Standard	Standard
Deck Deflector	OCDC -Operator Controlled Discharge Chute	OCDC -Operator Controlled Discharge Chute	OCDC -Operator Controlled Discharge Chute
Parking Brake	Standard - Drum	Standard - Drum	Standard - Drum
Body			
Frame	Welded 6 Rail Steel-tube	Welded 6 Rail Steel-tube	Welded 6 Rail Steel-tube
Fenders	Stainless Steel	Stainless Steel	Stainless Steel
Floor-pan	Flip-up, Stainless Steel with rubber mat	Flip-up, Stainless Steel with rubber mat	Flip-up, Stainless Steel with rubber mat
Seat	Deluxe Suspension Seat with Armrest	Deluxe Suspension Seat with Armrest	Deluxe Suspension Seat with Armrest
Engine Guard	Standard	Standard	Standard
Towing Capacity	2000 lbs	2000 lbs	2000 lbs
Mower Deck			
Deck Size	66 Inches	74 Inches	74 Inches
Construction	7 ga (.187") Formed & Welded	7 ga (.187") Formed & Welded	7 ga (.187") Formed & Welded
Top Plate	7 ga bolted not welded	7 ga bolted not welded	7 ga bolted not welded
Blades	3-23.3 Inch Blades	3-26 Inch Blades	3-26 Inch Blades
Tip Speed (Approximate)	19,031 fpm	19,144 fpm	19,144 fpm
Spindle Housings	1pc Keyless Sealed Cast Iron	1pc Keyless Sealed Cast Iron	1pc Keyless Sealed Cast Iron
Spindles	1.25" Effective diameter machined shaft	1.25" Effective diameter machined shaft	1.25" Effective diameter machined shaft
Anti-Scalp Rollers	Standard	Standard	Standard
Pulleys	Vented Split 3/16" Steel Deep Groove	Vented Split 3/16" Steel Deep Groove	Vented Split 3/16" Steel Deep Groove
Electric Deck Lift	Standard	Standard	Standard
Deck Quick Lift	Optional	Optional	Optional
Tires			
Rear Tires	25X12-9 Turf Boss III Tubeless 4ply	25X12-9 Turf Boss III Tubeless 4ply	27X12-9 Turf Boss VI Tubeless 4ply
Front Tires	15X6-8 Tubeless 4ply	15X6-8 Tubeless 4ply	15X6-8 Tubeless 4ply
Dimensions & Performance (Approximate)			
Acres/Hour	5.9 Acres Per Hour	6.6 Acres Per Hour	6.6 Acres Per Hour
Cutting Height	1.5 Inches to 5 Inches	1.5 Inches to 5 Inches	1.5 Inches to 5 Inches
Overall Height (with rollbar up)	76 Inches	76 Inches	76 Inches
Overall Height (with rollbar down)	50 Inches	49 Inches	49 Inches
Overall Width	72 Inches	76 Inches	76 Inches
Overall Length (with rollbar up)	84 Inches	86 Inches	86 Inches
Overall Length (with rollbar down)	101 Inches	102 Inches	102 Inches
Overall Weight	1445 Pounds	1502 Pounds	1538 Pounds

Specifications may change as we continually improve our mowers. For the latest information and mower specifications, please visit dixiechopper.com or visit your local Dixie Chopper dealer.

*The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only.

Revision 09/09/2011