



XCALIBER 4 X 4

The Dixie Chopper Xcaliber 4 X 4 combines four-wheel drive versatility with zero-turn maneuverability in a unique lawn-mowing machine. Powered by a 33HP Generac gasoline engine, the Xcaliber 4 X 4 makes hillsides and inclines readily accessible for quality mowing.

Up to a
5 Year
WARRANTY
Including a
3,000 Hour
Drivetrain Warranty
(See dealer for details)



4-post roll bar
factory standard



Caster Wheels

Electric actuator for fast and easy operation.
Thumb operated switch controls actuator.

Retractable
seat belt
with an aircraft
style buckle
for quick
release



Slope Indicator

Stainless
steel body

Turf Boss
Tires
27 Inch

Zero-turn
caster
wheels

Anti-scalp rollers

OCDC
Operator Controlled Discharge Chute

Model	Engine Horsepower	Deck Size	Acres Per Hour	Fuel Capacity
Xcaliber 4 X 4	Generac 33HP	56 Inches	5.0 Acres Per Hour	11 Gallons

Acres per hour is calculated on 80% operator accuracy and mowing conditions. Optimum cutting height 2.5" to 4.5" outside that range minor adjustment may be required. Visit dixiechopper.com or your local Dixie Chopper dealer for more information.

Revision 10/17/2011
Part Number 700216



XCALIBUR 4 X 4

3356

Engine	
Manufacturer	Generac
Horsepower*	33HP @ 3750RPM
Displacement	992cc
Crankshaft	Vertical Shaft
Oil System	Gear-Driven
Oil Safety Features	Low oil warning horn (98db)
Additional Filtration	Amsoil 1 Micron Filter
Air-Cleaner	Donaldson Dual Stage
Cooling	Air Cooled
Electrical	
Battery	12 Volt, 475cca - Standard
Charging System	20 Amp Alternator
Presence Control	Seat Switch Safety Shut-off
Hour Meter	Digital, Tachometer, Voltmeter, Service Alerts
Fuel System	
Fuel Type	Gasoline
Fuel Gauge	N/A
Fuel Capacity	11 Gallons
Fuel Valve	3 Position/Shut-off
Drive System	
Transaxle	N/A
Torqpack	N/A
Pumps	Hydro-Gear 21 Series
Wheelmotors	White 24 Cubic Inch
Controls	
Directional Control	Independent Steering Levers
Blade Engagement	PTO Switch
Deck Height Adjustments	Electric Lift, 1/4" increments
Ignition	Key Switch
Throttle/Choke	Standard
Deck Deflector	OCDG -Operator Controlled Discharge Chute
Parking Brake	Standard - Drum all 4 Drive Wheels
Body	
Frame	Welded 6 Rail Steel-tube
Fenders	Stainless Steel
Floor-pan	Flip-up, Stainless Steel with rubber mat
Seat	Deluxe Suspension Seat with Armrests
Engine Guard	Standard
Towing Capacity	2000 lbs
Mower Deck	
Deck Size	56 Inches
Construction	7 ga (.187") Formed & Welded
Top Plate	7 ga bolted not welded
Blades	3-20 Inch Blades
Tip Speed (Approximate)	18,934 fpm
Spindle Housings	1pc Keyless Sealed Cast Iron
Spindles	1.25" Effective diameter machined shaft
Anti-Scalp Rollers	Standard
Pulleys	Vented Split 3/16" Steel Deep Groove
Electric Deck Lift	Standard
Deck Quick Lift	Optional
Tires	
Rear Drive Tires	27X13-12 Turf Boss IV Tubeless 4ply
Front Drive Tires	27X13-12 Turf Boss V Tubeless 4ply
Front Casters	15X6-8 Tubeless 4ply
Dimensions & Performance (Approximate)	
Acres/Hour	5.0 Acres Per Hour
Cutting Height	1.5 Inches to 5 Inches
Overall Height (with rollbar up)	78 Inches
Overall Height (with rollbar down)	50 Inches
Overall Width	62 Inches
Overall Length (with rollbar up)	110 Inches
Overall Length (with rollbar down)	123 Inches
Overall Weight	1735 Pounds



The engine oil accumulator allows extra oil to be funneled from the system into the engine for adequate lubrication when accessing inclines.

