LIASSIC



MODELS:

2750KW 27hp, 50" Deck 2760KW 27hp, 60" Deck **3160KW** 31hp, 60" Deck **3572KW** 35hp, 72" Deck



A TRUE CLASSIC AMERICAN WORKHORSE.

The **Classic** is the perfect definition of a workhorse with the combination of commercial quality with industrial features.

- Power and More Power Powered by Kawasaki® FX engines up to 35 horsepower to power through the tough jobs with ease.
- Lifetime Warranty Frame The strongest frame in the industry with a 1"x 2" 7 gauge steel construction guaranteed not to break.
- Over-Sized Hydraulics Reduces the system pressure and backed with a 5-year/3,000 hour warranty.
- Complete Discharge Control An operator controlled discharge chute (OCDC) allows you to switch from normal discharge to closing the chute on the fly.
- Tried and True Decks Offered in three diverse deck widths (50", 60", and 72") the Elite X Deck has been the staple piece to Dixie Chopper's reputation of cleanly cutting all types of grass.
- **Comfort Package** Our suspension seat and unique Springer Forks comes standard on select Classic models to provide a smooth ride in all terrain.





High Performance Package - Comes standard on select models.



Pumps & Wheel Motors - Stronger transmissions for extended system life.



50", 60", and 72" Elite X Deck -Gives a quality cut in all types of grass



OCDC - Open and close the discharge chute on command



PEER® Spindles – Maintenance free with Contamination Exclusion Technology



*unlimited hour limited warranty



	50" Deck	60" Deck		72" Deck	
Model	2750KW	2760KW	3160KW	3572KW	
Engine					
Manufacturer	Kawasaki® FX				
Horsepower	27		31	35	
Displacement	852cc		999сс		
Air-cleaner	4 stage				
Cooling	Air cooled				
Starter	Electric				
Engine warranty	3 Year				

Drive System				
Pumps	Hydro-Gear® 16cc	Hydro-Gear® 21cc		
Wheel motors	Parker® DG280	Parker® DG335		
Ground speed	12 mph	13 mph		
Parking brake	Automotive Style			
Towing capacity	2000 lbs			

Mower Deck				
Deck size	50"	60"	72"	
Acres/hour*	4.8	5.8	7.5	
Cutting height	1.25" - 5"			
OCDC (operator controlled discharge chute)	Standard			
Deck height adjustments	Manual lift, 1/4" increments			
Electric lift	Optional			
Deck engagement	Ogura® 250 ft-lbs			
Construction	10 ga formed & welded 7 ga formed & we		7 ga formed & welded	
Top plate	7 ga bolted (not welded)			
Blades	3 - 17" x 2.5"	3 - 20.5" x 2.5"	3 - 24" x 2.5"	
Blade tip speed (approximate)	18,000 fpm			
Spindles	1.25" effective diameter machined shaft			
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)			
Spindle cooling fans	3			
Anti-scalp rollers	4 5		5	
Pulleys	Vented split 3/16" steel deep groove			

General				
Battery	12 Volt, 350cca			
Digital display	Tachometer, voltmeter, service alerts			
Fuel capacity	8 gallons	10 gallons	12 gallons	
Rear tires	25 x 12-12 GrassMaster			
Front tires	15 x 6-8			
Frame	Welded 1" x 2" tube, 7 ga formed			
Fenders	Stainless steel			
Floor-pan	Removable, steel			
Seat	Full suspension, adjustable seat w/ armrest			
Springer Forks	Optional Standard			

Dimensions				
Overall height	53"			
Overall height (rollbar up)	78"			
Overall width	55.5"	65.5"		76"
Overall length	77.5"		78"	79"
Overall length (rollbar down)	81"		83"	
Weight	1074 lbs	1134 lbs	1228 lbs	1425 lbs

