

EAGLE



MODELS:

2754KW 27hp, 54" Deck

2760KW 27hp, 60" Deck

COMMERCIAL



Eagle 2754KW shown*

LADIES AND GENTLEMEN, THE EAGLE HAS LANDED.

The new **Eagle** is here and ready to take on any job at hand. Loaded with commercial features, the Eagle delivers more speed, power, and performance to maintain your land.

- **Foot-Operated OCDC** – A foot-operated OCDC (operator-controlled discharge chute) allows you to keep your hands on the steering levers while closing the discharge chute on the fly.
- **Proven Power** – Equipped with the industry preferred Kawasaki® FX engines for trusted reliability and performance.
- **Deep Deck** – Offered in two cutting widths (54" and 60"), the Eagle's deck features a deep 7 gauge shell to handle more volume when tackling through tough grass.
- **Smooth AND Fast** – The Parker® HTG series transmissions deliver super smooth steering up to 12 miles per hour in a reliable and efficient drivetrain.
- **Enhanced Comfort** – Full suspension with a padded design and isolated platform provides ultimate comfort.
- **InCommand™ Console** – Full control at your fingertips. Features a keyless ignition, blade and job timer, tachometer, fuel gauge, and SoftStart clutch engagement.



OCDC – Foot-operated to keep your hands on the steering levers



InCommand™ Console – Keyless ignition, SoftStart clutch engagement, and more



Parker® HTG – Smooth steering and 1,000 hour oil change intervals



PEER® Spindles – Maintenance free with Contamination Exclusion Technology



54" and 60" Decks – Deep 7 gauge shell to tackle deep grass with ease

**3 YEAR
BUMPER-TO-BUMPER
WARRANTY***

*unlimited hour limited warranty

*Actual production model may vary

(765)-CHOPPER | www.dixiechopper.com



EAGLE

	54" Deck	60" Deck
Model	2754KW	2760KW
Engine		
Manufacturer	Kawasaki® FX	
Horsepower	27	
Displacement	852cc	
Air-cleaner	4 stage	
Cooling	Air cooled	
Starter	Electric	
Engine warranty	3 Year	

Drive System		
Dual hydrostatic	Parker® HTG (14cc)	
Ground speed	12 mph	
Parking brake	Integrated in transaxle	
Towing capacity	1000 lbs	

Mower Deck		
Deck size	54"	60"
Acres/hour	5.2	5.8
Cutting height	1" - 5"	
OCD (operator controlled discharge chute)	Foot-operated (standard)	
Deck height adjustments	Manual lift, 1/4" increments	
Electric lift	Optional	
Deck engagement	Warner® 250 ft-lbs with SoftStart	
Construction	7 ga formed & welded	
Blades	(3) - 2.5" x 19"	(3) - 2.5" x 20.5"
Blade tip speed (approximate)	18,500 fpm	
Spindles	1.25" effective diameter machined shaft	
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)	
Anti-scalp rollers	4	
Pulleys	7 ga steel deep groove	Vented split 3/8" steel deep groove

General		
Battery	12 Volt, 350cca	
Digital display	InCommand™ Console - Tachometer, hour meter, blade timer, fuel gauge, and ignition	
Fuel capacity	8 gallons	
Rear tires	25 x 12-12 GrassMaster	
Front tires	15 x 6-8	
Frame	Welded C-channel, 7 ga formed	
Floor-pan	Removable, steel	
Seat	Full suspension, adjustable seat w/ armrest and isolated platform	
Springer Forks	Optional	

Dimensions		
Overall height (rollbar down)	52.7"	
Overall height (rollbar up)	77.7"	
Overall width (chute down)	70.3"	76.9"
Overall width (chute up)	59.6"	66.1"
Overall length (rollbar down)	88.5"	
Overall length (rollbar up)	84.6"	
Weight	1306 lbs	1322 lbs