## CHLIBER



## **MODELS:**

3366KOE 33hp, 66" Deck 3566KW 35hp, 66" Deck 3574KW 35hp, 74" Deck



## THE CHOICE FOR **EXTREME PRODUCTIVITY.**

Professional commercial contractors and large property home owners have come to depend on the **XCaliber** for its legendary performance. Our flagship mower features:

- Pure Power Models powered with Kawasaki® FX or fuel efficient Kohler® EFI engines.
- X2 Wind Tunnel Deck The industry's best cutting deck available in 66" and 74" cutting widths for maximum productivity, while retaining the Wind Tunnel design and industry leading 2-inch blade overlap.
- **Comfort Package** Our suspension seat and unique Springer Forks make the XCaliber the smoothest riding mower on the market today.
- **Productivity** Our heavy-duty drivetrain of pumps and wheel motors increases ground speed up to 13 mph to mow over 7 acres per hour.
- Wide Wheelbase An extra wide wheelbase assists in hillside performance and overall ride quality.
- Most Lifetime Warranties Worry-free lifetime warranties on the frame, stainless steel, front forks, steering levers, and front caster bearings.



Total Comfort - Suspension seat and Springer Forks for highest quality ride.



12 Gallon Fuel Capacity - More fuel capacity eliminates frequent fill-ups



Pumps & Wheel Motors -Guaranteed for 5 years or 3,000 hours



PEER® Spindles – Maintenance free with Contamination Exclusion Technology



X2 "Wind Tunnel" Deck - Increases airflow and reduces build-up inside deck



\*unlimited hour limited warranty

<sup>\*</sup>Actual production model may vary



	66" Deck		74" Deck
Model	3366KOE	3566KW	3574KW
Engine			
Manufacturer	Kohler® EFI	Kawasaki® FX	
Horsepower	33	35	
Displacement	824cc	999cc	
Air-cleaner	4 stage		
Cooling	Air cooled		
Starter	Electric		
Engine warranty	3 Year		

Drive System		
Pumps	Hydro-Gear® 21cc	
Wheel motors	Parker® DG335	
Ground speed	13 mph	
Parking brake	Automotive Style	
Towing capacity	2000 lbs	

Mower Deck			
Deck size	66"	74"	
Acres/hour*	6.9	7.8	
Cutting height	1.25" - 5"		
OCDC (operator controlled discharge chute)	Standard		
Deck height adjustments	Manual lift, 1/4" increments		
Electric lift	Optional		
Deck engagement	Ogura® 250 ft-lbs		
Construction	7 ga formed & welded		
Top plate	7 ga bolted (not welded)		
Blades	3 - 23.3" x 2.5"	3 - 26" x 2.5"	
Blade tip speed (approximate)	18,000 fpm		
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)		
Spindles	1.25" effective diameter machined shaft		
Anti-scalp rollers	6		
Spindle cooling fans	3		
Pulleys	Vented split 3/16" steel deep groove		

General	
Battery	12 Volt, 350cca
Digital display	Tachometer & hour meter
Fuel capacity	12 gallons
Rear tires	25 x 12-12 GrassMaster
Front tires	15 x 6-8
Frame	Welded 1" x 2" tube, 7 ga formed
Fenders	Stainless steel
Floor-pan	Removable, steel
Seat	Full suspension, adjustable seat w/ armrest
Springer Forks	Standard

Dimensions		
Overall height	52"	53"
Overall height (rollbar up)	77.5"	
Overall width	72"	76"
Overall length	85"	86"
Overall length (rollbar down)	88.5"	89.5"
Weight	1445 lbs	1482 lbs

