FREE

COMMERCIAL

MODELS:

2754KW 27hp, 54" Deck 2760KW 27hp, 60" Deck NEW 3160KW 31hp, 60" Deck





LADIES AND GENTLEMEN, THE EAGLE HAS LANDED.

The **Eagle** is loaded with commercial features and delivers more speed, power, and performance to maintain your home's property, commercial accounts, and everything in between.

- Foot-Operated OCDC A foot-operated OCDC (operator-controlled discharge chute) allows you to take full control of your clippings.
- Proven Power Equipped with the industry preferred Kawasaki* FX engine up to 31hp for trusted reliability and performance.
- **Robust Deck** Offered in two cutting widths (54"and 60"), the Eagle's deck features a deep 7 gauge shell and **abrasion resistance baffles** to outlast the competition in extreme conditions.
- **Smooth AND Fast** The Parker* HTG series transmissions deliver a smooth drive up to 14 miles per hour in a reliable and efficient drivetrain.
- **Enhanced Comfort** Full suspension seat with a padded design and isolated platform provides ultimate comfort.
- Run-Flat Tires Flat tires are a problem of the past with run-flat tires standard on the Eagle.



OCDC - Foot-operated to keep your hands on the steering levers



Ultimate Comfort - ISO mounted suspension seat for all-day comfort



Parker' HTG - Smooth steering and 1,000 hour oil change intervals



Turbinator' Pre-Cleaner - Exclusive feature removes debris for cleaner air



54" and 60" Decks - Deep 7 gauge shell to tackle deep grass with ease



*Unlimited hour limited warranty, see dealer for complete warranty details



	54" Deck	60" Deck	
Model	2754KW	2760KW	3160KW (SS)
Engine			
Manufacturer	Kawasaki [®] FX		
Horsepower	27		31
Displacement	852cc		999cc
Air-cleaner	4 stage & Turbinator® Pre-Cleaner		
Cooling	Air-cooled		
Starter	Electric		
Engine warranty	3-Year		

Drive System		
Dual hydrostatic	Parker®HTG (14cc)	Parker®HTG (16cc)
Ground speed	12 mph	14 mph
Parking brake	Integrated in transaxle	
Towing capacity	1,000 lbs	

Mower Deck			
Deck size	54"	60"	
Acres/hour	5.2	5.8	6.7
Cutting height	1" - 5"		
OCDC (operator controlled discharge chute)	Foot-operated (standard)		
Deck height adjustments	Manual lift, 1/4" increments		
Electric lift	Optional		
Deck engagement	Warner® 250 ft-lbs		
Construction	7 ga formed & welded, Abrasion Resistance Baffles		
Blades	(3) - 2.5" x 19"	(3) - 2.5" x 20.5"	
Blade tip speed (approximate)	18,500 fpm		
Spindles	1.25" effective diameter machined shaft		
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)		
Anti-scalp rollers	4		
Pulleys	7 ga steel deep groove	Vented split 3/8" steel deep groove	

General			
Battery	12 Volt, 350cca		
Digital Display	Tachometer, hour meter, fuel gauge		
Fuel capacity	8 gallons		
Rear tires	25 x 12-12 GrassMaster		
Front tires	15 x 6-8 (run-flat)		
Frame	Welded C-channel, 7 ga formed		
Floor-pan	Removable, steel		
Seat	Full suspension, adjustable seat w/ armrests and isolated platform		
Springer Forks	Optional	Standard	

Dimensions			
Overall height (rollbar down)	52.7"		
Overall height (rollbar up)	77.7"		
Overall width (chute down)	70.3" 76.9"		
Overall width (chute up)	59.6" 66.1"		
Overall length (rollbar down)	88.5"		
Overall length (rollbar up)	84.6"		
Weight	1306 lbs	1322 lbs	1346 lbs

