

XCALIBER™

INDUSTRIAL



MODELS:

3566KW 35hp, 66" Deck

NEW 4066VGE 40hp, 66" Deck

3574KW 35hp, 74" Deck

NEW 4074VGE 40hp, 74" Deck



XCaliber 3566KW shown*

THE TOUGHEST MOWER IN THE ZERO-TURN INDUSTRY.

Professional commercial contractors and large property home owners have come to depend on the **XCaliber** for its legendary performance. Our flagship mower features:

- **Pure Power** – Models powered with Kawasaki® FX or fuel efficient Vanguard® Big Block EFI engines.
- **X2 Wind Tunnel Deck** – The industry's best cutting deck available in 66" and 74" cutting widths for maximum productivity, "Wind Tunnel" front edge for increased discharge performance, and industry leading 2-inch blade overlap for precision cutting.
- **Comfort Package** – A high-back suspension seat and unique Springer Forks provide a comfortable ride for the operator day in and day out.
- **Productivity** – Our heavy-duty drivetrain of pumps and wheel motors increases ground speed up to 13 mph to mow over 7 acres per hour.
- **Wide Wheelbase** – An extra wide wheelbase assists in hillside performance and overall ride quality.
- **Most Lifetime Warranties** – Worry-free lifetime warranties on the frame, stainless steel, front forks, steering levers, and front caster bearings.



Total Comfort – Suspension seat with recline, lumbar, and padded armrests



Springer Forks – Absorb bumps for comfort and increased productivity



Pumps & Wheel Motors – Stronger transmissions for extended system life



Turbinator® Pre-Cleaner – Exclusive feature removes debris for cleaner air



Wind Tunnel Deck – Increases airflow and reduces build-up under deck

3 YEAR
BUMPER-TO-BUMPER
WARRANTY*

*Unlimited hour limited warranty, see dealer for complete warranty details



X-CALIBER™

	66" Deck		74" Deck	
Model	3566KW	4066VGE	3574KW	4074VGE
Engine				
Manufacturer	Kawasaki® FX	Vanguard® EFI	Kawasaki® FX	Vanguard® EFI
Horsepower	35	40	35	40
Displacement	999	993cc	999cc	993cc
Air-cleaner	4 stage & Turbinator® Pre-Cleaner			
Cooling	Air-cooled			
Starter	Electric			
Engine warranty	3-Year			

Drive System	
Pumps	Hydro-Gear® 21cc
Wheel motors	Parker® DG335
Ground speed	13 mph
Parking brake	Automotive Style
Towing capacity	2,000 lbs

Mower Deck	
Deck size	66" 74"
Acres/hour*	6.9 7.8
Cutting height	1.25" - 5"
OCDC (operator controlled discharge chute)	Standard
Deck height adjustments	Manual lift, 1/4" increments
Electric lift	Optional
Deck engagement	Ogura® 250 ft-lbs
Construction	7 ga formed & welded
Top plate	7 ga bolted (not welded)
Blades	3 - 23.3" x 2.5" 3 - 26" x 2.5"
Blade tip speed (approximate)	18,000 fpm
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)
Spindles	1.25" effective diameter machined shaft
Anti-scalp rollers	6
Spindle cooling fans	Standard (3)
Pulleys	Vented split 3/16" steel deep groove

General	
Battery	12 Volt, 350cca
Digital display	Tachometer, hour meter, voltmeter, service alerts
Fuel capacity	12 gallons
Rear tires	25 x 12-12 GrassMaster
Front tires	15 x 6-8 15 x 6-8 (run-flat)
Frame	Welded 1" x 2" tube, 7 ga formed
Fenders	Stainless steel
Floor-pan	Removable, steel
Seat	High-back, full suspension, lumbar, recline, and padded armrests
Springer Forks	Standard

Dimensions	
Overall height	52" 53"
Overall height (rollbar up)	77.5"
Overall width	72" 76"
Overall length	85" 86"
Overall length (rollbar down)	88.5" 89.5"
Weight	1445 lbs 1482 lbs