

ZEE 2 HP™

RESIDENTIAL

MODELS:

2448KW 24hp, 48" Deck

2454KW 24hp, 54" Deck



Zee 2 HP - 2454KW model shown*

REDEFINING THE RESIDENTIAL MOWER.

- **High Horsepower** – A 24 horsepower engine from Kawasaki® for proven power to tackle through thick grass up to 3.4 acres per hour.
- **Full Clipping Control** – The OCDC comes standard to give you full control of your clippings. Keep grass out of the driveway, flower bed, and more.
- **Superior Comfort** – A super plush seat with 360 ISO Mounts give the operator extra comfort for extended mowing periods.
- **Hydro-Gear® Drivetrain** – ZT-3100 commercial-grade transaxles offer steel-cut gears, charge pumps, and shock valves for extended drivetrain performance.
- **Large Drive Tires** – 22" rear drive tires provide more speed, stability, and traction when you need it.
- **Elite Cutting System** – Offered in two cutting widths (48" and 54"), the Elite Deck easily cuts large volumes of grass with a manicured finish.
- **Industry Leading Warranty** – Enjoy peace-of-mind with three years of warranty with unlimited hours of residential use and industry leading lifetime warranties.




Discharge Chute – Take full control of clippings with the OCDC



Large Rear Tires – More traction, more speed, and better stability



Hydro-Gear® ZT-3100 – Commercial duty drivetrain with serviceable filters



Comfort Ride – 360 ISO Mount with plush cushion seat for superior comfort



Proven Power – 24hp Kawasaki engine for more performance and reliability

3 YEAR
BUMPER-TO-BUMPER
WARRANTY*

*Unlimited hour limited residential warranty, see dealer for complete warranty details



ZEE 2 HP™

	48" Deck	54" Deck
Model	2448KW	2454KW
Engine		
Manufacturer	Kawasaki® FR	
Horsepower	24	
Displacement	726cc	
Air-cleaner	2 stage	
Cooling	Air-cooled	
Starter	Electric	
Engine warranty	3-Year	

Drive System		
Dual hydrostatic	Hydro-Gear® ZT-3100 transaxles (internal expansion tank)	
Ground speed	8 mph	
Parking brake	Integrated in transaxle	
Towing capacity	100 lbs	

Mower Deck		
Deck size	48"	54"
Acres/hour*	3.1	3.4
Cutting height	1.5" - 4.5"	
Deck height adjustments	Manual lift, 1/2" increments	
Deck Quick-Lift	Integrated	
Deck engagement	Ogura® 87 ft-lbs	
Construction	10 ga formed & welded	
Blades	3 - 17.25" x 2.5"	3 - 19.25" x 2.5"
Blade tip speed (approximate)	18,500 fpm	
Spindles	.75" effective diameter machined shaft	
Spindle housings	1pc keyless sealed cast aluminum	
Anti-scalp rollers	4	
Pulleys	Vented split 3/16" steel deep groove	

General		
Battery	12 Volt, 300cca	
Digital display	Hour meter	
Fuel capacity	4 gallons	
Rear tires	22 x 11-10	
Front tires	13 x 6.5-6	
Frame	Welded 1" x 2", 2" x 2" tube, 10 ga formed	
Fenders	Stainless steel	
Floor-pan	Removable, steel	
Seat	20" padded seat w/ armrests, ISO 360 Mount	

Dimensions		
Overall height	47"	
Overall width (chute down)	53"	59"
Overall width (chute up)	57.25"	63.25"
Overall length	76"	
Weight	775 lbs	788 lbs