

MEET THE HARDEST WORKER ON THE JOB SITE.

Dixie Chopper is now known for more than mowers. Meet the Talon M/S, a heavy-duty mini-skid-steer built for commercial contractors who do more than mowing. This new model is loaded with features, including:

- **Diesel Power** Reliability and efficient power comes standard with the Kubota D1105 diesel engine.
- **Gate Friendly** The 700HPX offers a hydraulically expandable undercarriage to retract the unit width less than 36" to fit in tight spaces.
- **Hydraulic Flow** Delivering up to 11.3 gpm to the auxiliary hydraulic flow, the Talon M/S attachments make easy work of tough jobs.
- All-Day Comfort The spring assisted stand-on platform design with generous hip padding provide operator comfort from start to finish.
- **Productivity** With the expandable undercarriage and speeds up to 4.5 mph, operators can safely and quickly get work done in record time.
- **Compatibility** Universal compact utility loader mounting plate and quick-attach system to easily switch between most standard attachments.

AVAILABLE ACCESSORIES

- Pallet Forks
- Auger
- Bucket
- Blade
- Grapple
- Sweeper



Kubota Diesel - Quiet, powerful, and reliable diesel engine



Narrow Minded - Fits through smaller gates when needed



Heavy Loads - Get more work done with 700+ pounds of operating capacity



*Unlimited hour limited warranty, see dealer for complete warranty details





Model	700HPX
Engine	
Manufacturer	Kubota*
Horsepower	24.8
Fuel Type	Diesel
Fuel capacity	9 gallons
Cooling	Liquid
Starter	Electric
Engine warranty	2-Year

Hydraulic System	
Hydraulic capacity	24 gallons
System flow (total)	27.1 GPM
Hydraulic flow aux (high/low)	11.3 (high), 8.7 (low) GPM
Hydraulic flow (drive)	7.1 GPM
System pressure	3000 PSI
Tracks	
Track gauge	33.75"
Track width	9"
Ground speed	4.5 MPH
Ground Pressure	4.21 PSI

Dimensions	
Weight (no attachment)	2880 lbs
Length (no attachment)	77"
Length (with bucket)	96"
Width (fully retracted)	34.5"
Width (fully extended)	43.5"
Height (boom lowered)	54"
Height (boom raised)	98"
Hinge pin height	77"
Dump height	60"
Dump angle	37 degrees
Reach	34"
Tip capacity	2020 lbs
Operating capacity (35% of tip load)	707 lbs
Ground clearance	5"

