

# ZEE 2™



## RESIDENTIAL

### MODELS:

2342KW 23hp, 42" Deck

2348KW 23hp, 48" Deck

2354KW 23hp, 54" Deck



Zee 2 - 2348KW shown\*

## THE MOWER WITH MORE MUSCLE FOR YOUR MONEY.

- **High Horsepower** - A 23 horsepower engine from Kawasaki\* to power through thick grass up to 3.1 acres per hour.
- **Elite Cutting System** - Offered in three cutting widths (42", 48", and 54"), the Elite Deck easily cuts large volumes of grass and provides an attractive after-cut appearance.
- **7-Stage Deck Height** - Allows you to quickly and easily adjust mowing height for different applications.
- **Hydro-Gear® ZT-2800 Transaxles** - Proven and reliable transmissions with an external oil filter for easier maintenance and extended system life.
- **Quick-Lift Lock** - Allows you to quickly raise the deck to avoid objects and locks the deck in travel height for transporting or storing.
- **Steel Fenders** - Built with 14-gauge steel, the fenders protect the body and fuel tank from damage.
- **Industry Leading Warranty** - Backed with a three year warranty with unlimited hours of residential use and industry leading lifetime warranties.



**Steel Fenders** - Protects fuel tank from sun and impact damage



**Commercial Forks** - Greaseable and lifetime warranty against breakage



**Hydro-Gear® ZT-2800** - Smooth operation and fully serviceable



**Comfort Ride** - Plush cushioned seat with armrests for extra comfort



**42", 48", & 54" Elite Cutting System** - Formed and welded 10-ga deck shell

**3 YEAR**  
BUMPER-TO-BUMPER  
WARRANTY\*

\*Unlimited hour limited residential warranty, see dealer for complete warranty details



# ZEE 2™

	42" Deck	48" Deck	54" Deck
<b>Model</b>	<b>2342KW</b>	<b>2348KW</b>	<b>2354KW</b>
<b>Engine</b>			
<b>Manufacturer</b>	Kawasaki® FR		
<b>Horsepower</b>	23		
<b>Displacement</b>	726cc		
<b>Air-cleaner</b>	2 stage		
<b>Cooling</b>	Air-cooled		
<b>Starter</b>	Electric		
<b>Engine warranty</b>	3-Year		

<b>Drive System</b>			
<b>Dual hydrostatic</b>	Hydro-Gear® ZT-2800 transaxles (internal expansion tank)		
<b>Ground speed</b>	7 mph		
<b>Parking brake</b>	Integrated in transaxle		
<b>Towing capacity</b>	100 lbs		

<b>Mower Deck</b>			
<b>Deck size</b>	42"	48"	54"
<b>Acres/hour*</b>	2.4	2.7	3.1
<b>Cutting height</b>	1.5" - 4.5"		
<b>Deck height adjustments</b>	Manual lift, 1/2" increments		
<b>Deck Quick-Lift</b>	Integrated		
<b>Deck engagement</b>	Ogura® 87 ft-lbs		
<b>Construction</b>	10 ga formed & welded		
<b>Blades</b>	3 - 15.25" x 2.5"	3 - 17.25" x 2.5"	3 - 19.25" x 2.5"
<b>Blade tip speed (approximate)</b>	18,500 fpm		
<b>Spindles</b>	.75" effective diameter machined shaft		
<b>Spindle housings</b>	1pc keyless sealed cast aluminum		
<b>Anti-scalp rollers</b>	4		
<b>Pulleys</b>	Vented split 3/16" steel deep groove		

<b>General</b>			
<b>Battery</b>	12 Volt, 300cca		
<b>Digital display</b>	hour meter		
<b>Fuel capacity</b>	4 gallons		
<b>Rear tires</b>	20 x 8-10 GrassMaster	20 x 10-8 GrassMaster	
<b>Front tires</b>	13 x 6.5-6		
<b>Frame</b>	Welded 1" x 2", 2" x 2" tube, 10 ga formed		
<b>Floor-pan</b>	Removable, steel		
<b>Seat</b>	20" padded seat w/ armrests		

<b>Dimensions</b>			
<b>Overall height</b>	47"		
<b>Overall width (with chute)</b>	51.5"	57.5"	64"
<b>Overall length</b>	76"		
<b>Weight</b>	730 lbs	750 lbs	763 lbs