COMMERCIAL MODELS: 2448KW 24hp, 48" Deck 2454KW 24hp, 54" Deck

DIXIE CHOPPER



2460KW 24hp, 60" Deck

The **BlackHawk** is built to redefine your mowing experience with superior value, advanced operator controls, commercial grade components, and unmatched performance.

- **Proven Power -** Equipped with 24 horsepower Kawasaki* engines for years of trusted reliability and performance.
- **Robust Deck** Offered in three cutting widths, the BlackHawk deck features a deep 7 gauge shell and **abrasion resistance baffles** to outlast the competition in extreme conditions.
- **Smoothest Steering** The Parker* transmissions offer super smooth steering up to 9 miles per hour in a compact, quiet, and efficient drivetrain.
- **Total Comfort** The padded and over-sized bolstered seat hugs your torso for ultimate comfort.
- **Peer' Turf Xtreme™ Spindles** Maintenance free and constructed of high-strength ductile iron.
- **R.O.P.S.** Roll-over protection system comes standard to keep operators safe.
- **Ready to Accessorize** The BlackHawk is ready to add a suite of accessories including Springer Forks, suspension seat, light kit, striping kit, and more.



Kawasaki Engines - Reliable power to tackle the toughest jobs



Parker HTE - Smooth steering and 1,000 hour oil change intervals



48", 54", and 60" Decks - Deep 7 gauge shell to tackle deep grass



BlackHawk 2454KW shown

Hitch Receiver - Class 1 hitch for easier mounting of accessories



PEER* Spindles - Maintenance free with Contamination Exclusion Technology



*Unlimited hour limited warranty, see dealer for complete warranty details





	48" Deck	54" Deck	60" Deck	
Model	2448KW	2454KW	2460KW	
Engine				
Manufacturer	Kawasaki* FT			
Horsepower	24			
Displacement	726cc			
Air-cleaner	2 stage			
Cooling	Air-cooled			
Starter	Electric			
Engine warranty	3-Year			

Drive System				
Dual hydrostatic	Parker® HTE			
Ground speed	9 mph			
Parking brake	Integrated in transaxle			
Towing capacity	200 lbs			

Mower Deck				
Deck size	48"	54"	60"	
Acres/hour*	3.4	3.9	4.3	
Cutting height	1" - 5"			
OCDC (operator controlled discharge chute)	Optional accessory (foot-operated)			
Deck height adjustments	Manual lift, 1/4" increments			
Electric lift	Optional			
Deck engagement	Ogura" 150 ft-lbs			
Construction	7 ga formed & welded, Abrasion Resistance Baffles			
Blades	(3) -2.5" x 17"	(3) - 2.5" × 19"	(3) - 2.5" x 20.5"	
Blade tip speed (approximate)	18,500 fpm			
Spindles	1.25" effective diameter machined shaft			
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)			
Anti-scalp rollers	4			
Pulleys	7 ga steel deep groove		Vented split 3/8"steel deep groove	

General				
Battery	12 Volt, 350cca			
Digital Display	Tachometer, hour meter, fuel gauge			
Fuel capacity	7 gallons			
Rear tires	23 x 10.5-12 GrassMaster			
Front tires	13 × 6.5-6			
Frame	Welded C-channel, 7 ga formed			
Floor-pan	Removable, steel			
Seat	High-back adjustable padded seat w/ armrests			
Springer Forks	Optional accessory			

Dimensions						
Overall height (rollbar down)	50"					
Overall height (rollbar up)	71"					
Overall width (chute down)	63.6"	69.6"	76"			
Overall width (chute up)	49.2"	55.4"	61.9"			
Overall length (rollbar down)	85.8"					
Overall length (rollbar up)	81.3"					
Weight	1104 lbs	1114 lbs	1121 lbs			

