

THE ULTIMATE MOWING EXPERIENCE.

The new **Eagle HP** provides the ultimate mowing experience with unmatched combination of speed, power, performance, and comfort.

- Fast Ground Speed Hydro-Gear® ZT-5400 gives operators speeds up to 14mph for faster ground transportation and increased productivity.
- **Pure Power -** Equipped with the industry preferred Kawasaki* FX engine or a 40hp Vanguard* Big Block EFI for more power and fuel savings.
- **Ultimate Comfort** Springer Forks come standard along with a high-back seat with padded armrests, recline, lumbar, and isolated platform.
- **Robust Deck** Offered in two cutting widths (60"and 72"), the Eagle HP deck features a deep 7 gauge shell and **abrasion resistance baffles** to outlast the competition in extreme conditions.
- **Wide Stance** Extra-wide frame offers enhanced operator comfort and improved stability when mowing hillsides.
- **Run-Flat Tires** Flat tires are a problem of the past with run-flat tires standard on the Eagle HP.



Hydro-Gear ZT-5400 - Speeds up to 14mph for increased productivity



Suspension Seat - High back, padded armrests, and isolated platform



60" and 72" Decks - Deep 7 gauge shell to tackle deep grass with ease



More Muscle - Engines up to 40hp and Turbinator* Pre-Cleaner



Springer Forks - Absorb bumps to provide smoother ride for operator



*Unlimited hour limited warranty, see dealer for complete warranty details





	60" Deck		72" Deck	
Model	3560KW	4060VGE	3572KW	4072VGE
Engine				
Manufacturer	Kawasaki* FX	Vanguard® EFI	Kawasaki [®] FX	Vanguard® EFI
Horsepower	35	40	35	40
Displacement	999cc	993cc	999cc	993cc
Air-cleaner	4 stage & Turbinator® Pre-Cleaner			
Cooling	Air-cooled			
Starter	Electric			
Engine warranty	3-Year			

Drive System			
Dual hydrostatic	Hydro-Gear® ZT-5400		
Ground speed	14 mph		
Parking brake	Integrated in transaxle		
Towing capacity	300 lbs (low-speed only)		

Mower Deck					
Deck size	60"	72"			
Acres/hour	6.7	8.1			
Cutting height	1" - 5"				
OCDC (operator controlled discharge chute)	Optional accessory (foot-operated)				
Deck height adjustments	Manual lift, 1/4" increments				
Electric lift	Optional				
Deck engagement	Warner® 250 ft-lbs				
Construction	7 ga formed & welded, Abrasion Resistance Baffles				
Blades	(3) - 2.5" x 20.5"	(3) - 2.5" 24.5"			
Blade tip speed (approximate)	18,500 fpm				
Spindles	1.25" effective diameter machined shaft				
Spindle housings	Peer* Turf Xtreme™ ductile iron (sealed)				
Anti-scalp rollers	4				
Pulleys	Vented split 3/8" steel deep groove				

General			
Battery	12 Volt, 350cca		
Digital Display	Hour meter, fuel gauge		
Fuel capacity	10 gallons		
Rear tires	25 x 12-12 GrassMaster		
Front tires	15 x 6-8 (run-flat)		
Frame	Welded C-channel, 7 ga formed		
Floor-pan	Removable, steel		
Seat	High-back, full suspension, lumbar, recline, padded armrests, and isolated platform		
Springer Forks	Standard		

Dimensions					
Overall height (rollbar down)	55.25"				
Overall height (rollbar up)	78.5"				
Overall width (chute down)	77"		89.6"		
Overall width (chute up)	67"		79.6"		
Overall length (rollbar down)	88.6"	90.9"	90.5"	92.8"	
Overall length (rollbar up)	88.5"		90.4		
Weight	1478 lbs	1466 lbs	1527 lbs	1515 lbs	

