

LADIES AND GENTLEMEN, THE EAGLE HAS LANDED.

The **Eagle** is loaded with commercial features and delivers more speed, power, and performance to maintain your home's property, commercial accounts, and everything in between.

- **Proven Power -** Equipped with the industry preferred 27 horsepower Kawasaki* FX engine for trusted reliability and performance.
- **Robust Deck** Offered in two cutting widths (54"and 60"), the Eagle's deck features a deep 7 gauge shell and **abrasion resistance baffles** to outlast the competition in extreme conditions.
- **Smooth AND Fast** The Parker* HTG series transmissions deliver a smooth drive up to 12 miles per hour in a reliable and efficient drivetrain.
- **Enhanced Comfort** Full suspension seat with a padded design and isolated platform provides ultimate comfort.
- Large Drive Tires 25" rear tires for more speed, stability, and operator comfort.
- Run-Flat Tires Flat front tires are a problem of the past with run-flat tires standard on the Eagle.



Ultimate Comfort - ISO mounted suspension seat for all-day comfort



Parker' HTG - Smooth steering and 1,000 hour oil change intervals



54" and 60" Decks - Deep 7 gauge shell to tackle deep grass with ease



Run-Flat Tires - Flat tires are a problem of the past



Turbinator Pre-Cleaner - Exclusive feature removes debris for cleaner air



*Unlimited hour limited warranty, see dealer for complete warranty details





	54" Deck	60" Deck	
Model	2754KW	2760KW	
Engine			
Manufacturer	Kawasaki* FX		
Horsepower	27		
Displacement	852cc		
Air-cleaner	4 stage & Turbinator* Pre-Cleaner		
Cooling	Air-cooled		
Starter	Electric		
Engine warranty	3-Y	3-Year	

Drive System		
Dual hydrostatic	Parker* HTG (14cc)	
Ground speed	12 mph	
Parking brake	Integrated in transaxle	
Towing capacity	1,000 lbs	

Mower Deck		
Deck size	54"	60"
Acres/hour	5.2	5.8
Cutting height	1" - 5"	
OCDC (operator controlled discharge chute)	Optional accessory (foot-operated)	
Deck height adjustments	Manual lift, 1/4" increments	
Electric lift	Optional	
Deck engagement	Warner* 250 ft-lbs	
Construction	7 ga formed & welded, Abrasion Resistance Baffles	
Blades	(3) - 2.5" x 19"	(3) - 2.5" x 20.5"
Blade tip speed (approximate)	18,500 fpm	
Spindles	1.25" effective diameter machined shaft	
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)	
Anti-scalp rollers	4	
Pulleys	7 ga steel deep groove	Vented split 3/8" steel deep groove

General		
Battery	12 Volt, 350cca	
Digital Display	Tachometer, hour meter, fuel gauge	
Fuel capacity	8 gallons	
Rear tires	25 x 12-12 GrassMaster	
Front tires	15 x 6-8 (run-flat)	
Frame	Welded C-channel, 7 ga formed	
Floor-pan	Removable, steel	
Seat	Full suspension, adjustable seat w/ armrests and isolated platform	
Springer Forks	Optional	

Dimensions		
Overall height (rollbar down)	52.7"	
Overall height (rollbar up)	77.7"	
Overall width (chute down)	70.3"	76.9"
Overall width (chute up)	59.6"	66.1"
Overall length (rollbar down)	88.5"	
Overall length (rollbar up)	84.6"	
Weight	1306 lbs	1322 lbs

