

## **THE TOUGHEST MOWER IN** THE ZERO-TURN INDUSTRY.

Professional commercial contractors and large property home owners have come to depend on the **XCaliber** for its legendary performance. Our flagship mower features:

- Pure Power Models powered with Kawasaki\* FX or Vanguard® Big Block EFI engines up to 40 horsepower.
- X2 Wind Tunnel Deck The industry's best cutting deck available in 66" and 74" cutting widths for maximum productivity, "Wind Tunnel" front edge for increased discharge performance, and industry leading 2-inch blade overlap for precision cutting.
- **Ultimate Comfort** Springer Forks come standard along with a high-back seat with padded armrests, recline, and lumbar.
- **Productivity** Our heavy-duty pump and wheel motor drivetrain increases ground speed up to 13 mph to mow over 7 acres per hour.
- Wide Wheelbase An extra wide wheelbase assists in hillside performance and overall ride quality.
- Most Lifetime Warranties Worry-free lifetime warranties on the frame, front forks, steering levers, and front caster bearings.



Total Comfort - Suspension seat with recline, lumbar, and padded armrests



Spindle Package - Maintenance-free spindles and cooling fans come standard



Wind Tunnel Deck - Increases airflow



Pumps & Wheel Motors - Stronger transmissions for extended system life



Springer Forks - Absorb bumps to provide smoother ride for operator



\*Unlimited hour limited warranty, see dealer for complete warranty details





	66"	Deck	74"	Deck
Model	3566KW	4066VGE	3574KW	4074VGE
Engine				
Manufacturer	Kawasaki <sup>®</sup> FX	Vanguard* EFI	Kawasaki* FX	Vanguard® EFI
Horsepower	35	40	35	40
Displacement	999	993cc	999cc	993cc
Air-cleaner	4 stage & Turbinator® Pre-Cleaner			
Cooling		Air-cooled Air-cooled		
Starter	Electric			
Engine warranty	3-Year			

<b>Drive System</b>		
Pumps	Hydro-Gear* 21cc	
Wheel motors	Parker DG335	
Ground speed	13 mph	
Parking brake	Automotive Style	
Towing capacity	2,000 lbs	

Mower Deck			
Deck size	66"	74"	
Acres/hour*	6.9	7.8	
Cutting height	1.25" - 5"		
OCDC (operator controlled discharge chute)	Standard		
Deck height adjustments	Manual lift, 1/4" increments		
Electric lift	Optional		
Deck engagement	Ogura® 250 ft-lbs		
Construction	7 ga formed & welded		
Top plate	7 ga bolted (not welded)		
Blades	3 - 23.3" x 2.5"	3 - 26" × 2.5"	
Blade tip speed (approximate)	18,000 fpm		
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)		
Spindles	1.25" effective diameter machined shaft		
Anti-scalp rollers	6		
Spindle cooling fans	Standard (3)		
Pulleys	Vented split 3/16" steel deep groove		

General		
Battery	12 Volt, 350cca	
Digital display	Tachometer, hour meter, voltmeter, service alerts	
Fuel capacity	12 gallons	
Rear tires	25 x 12-12 GrassMaster	
Front tires	15 x 6-8 15 x 6-8 (run-flat)	
Frame	Welded 1" x 2" tube, 7 ga formed	
Floor-pan	Removable, steel	
Seat	High-back, full suspension, lumbar, recline, and padded armrests	
Springer Forks	Standard	

Dimensions					
Overall height	52"	53"			
Overall height (rollbar up)	77.5"				
Overall width	72"	76"			
Overall length	85"	86"			
Overall length (rollbar down)	88.5"	89.5"			
Weight	1445 lbs	1482 lbs			

